



### A-B NON REPAIRABLE AREA

7.00-8.75	3"	75 mm
9.00-14.00	4"	100 mm
16.00-18.00	5"	125 mm
21.00-27.00	6"	150 mm

### NON-REPAIRABLE AREA - TRACTOR

14.9-20.8	4"	100 mm
23.1 and above	5"	125 mm

## Bias ply tyre Repair Chart

### SIZE OF INJURY



PLY RATING	Inch	1/8"	1/4"	3/8"	1/2"	3/4"	1"	1 1/2"	2"	2 1/2"	3"	4"	4 1/2"	5"
	mm	3	6	10	13	20	25	40	50	65	75	100	115	125
4	CBP 0	CBP 0	CBP 1	CBP 2	CBP 3	CBP 3	CBP 4	CBP 5						
6-8	CBP 0	CBP 1	CBP 2	CBP 3	CBP 3	CBP 4	CBP 4	CBP 5						
10-12	CBP 0	CBP 1	CBP 2	CBP 3	CBP 4	CBP 4	CBP 5	CBP 6	CBP 6	CBP 7	CBP 8			
14-16	CBP 0	CBP 1	CBP 3	CBP 4	CBP 4	CBP 5	CBP 6	CBP 6	CBP 7	CBP 7	CBP 8	CBP 8	CBP 9	CBP 10
18-20	CBP 0	CBP 1	CBP 4	CBP 4	CBP 5	CBP 6	CBP 6	CBP 7	CBP 8	CBP 8	CBP 9	CBP 9	CBP 10	CBP 10
20-22	CBP 0	CBP 1	CBP 4	CBP 5	CBP 6	CBP 7	CBP 8	CBP 8	CBP 9	CBP 9	CBP 9	CBP 9	CBP 10	CBP 10

This chart is a guideline only. Consult tyre manufacturer for repair limitations.

For sidewall repairs use CSP series patches instead of CBP series patches.

## For ply damages upto half of the carcass thickness on Tread, Shoulder, Sidewall

### SIZE OF INJURY



PLY RATING	Inch	1/8"	3/8"	1/2"	1"	2"	3"	4"	5"
	mm	3	10	13	25	50	75	100	125
8-12	CBP 0	CBP 1	CBP 2	CBP 3	CBP 4	CBP 4	CBP 6	CBP 7	CBP 8
14-18	CBP 0	CBP 1	CBP 2	CBP 4	CBP 5	CBP 5	CBP 6	CBP 7	CBP 8
20-22	CBP 0	CBP 2	CBP 3	CBP 5	CBP 6	CBP 6	CBP 7	CBP 8	CBP 9

This chart is a guideline only. Consult tyre manufacturer for repair limitations.

For sidewall repairs use CSP series patches instead of CBP series patches.

## Tractor Tyre Repair Chart

### SIZE OF INJURY



PLY RATING	Inch	2"	3"	4"	5"	6"	7"
	mm	50	75	100	125	150	175
4 - 6	CBP 5	CTP 1	CTP 1	CTP 2	CTP 2	CTP 2	CTP 3
8 - 12	CTP 4	CTP 4	CTP 4	CTP 5	CTP 5	CTP 5	CTP 6
14 - 16	CTP 4	CTP 5	CTP 5	CTP 5	CTP 6	CTP 6	CTP 7

This chart is a guideline only. Consult tyre manufacturer for repair limitations.